

RC10GT GEAR CHART

ASSOCIATED PART NUMBERS

Spur Gears		Clutch Bells	
66	7663	18	7608
64	7662	17	7607
62	7674	16	7606
60	8920	15	7604
58	8918	14	7609
56	8916	24	8904
		23	8902

RC10GT 2.6 TRANSMISSION

HOW TO USE THIS CHART:

Use the correct range of clutch bell according to whether you use 64T or 66T spur gear, and take into account if you use pull start or non pull start motor mounts.

Associated recommends **64T & 66T** spurs for typical GT off road applications.

For columns of 19T to 22T clutch bells, use aftermarket clutch bells.

	Associated gears applicable for this range. 64T & 66T recommended for off road GT										
	Range for 66T in new GT chassis, pull start motor mount										
	Range for 64T in new GT chassis, pull start motor mount										
	Range for 66T in new GT chassis, non pull start motor mount										
	64T in new GT chassis, non pull start mount					Aftermarket clutch bells					
	14	15	16	17	18	19	20	21	22	23	24
66	12.257	11.440	10.725	10.094	9.533	9.032	8.580	8.171	7.800	7.461	7.150
64	11.886	11.093	10.400	9.788	9.244	8.758	8.320	7.924	7.564	7.235	6.933
62	11.514	10.747	10.075	9.482	8.956	8.484	8.060	7.676	7.327	7.009	6.717
60	11.143	10.400	9.750	9.176	8.667	8.211	7.800	7.429	7.091	6.783	6.500
58	10.771	10.053	9.425	8.871	8.378	7.937	7.540	7.181	6.855	6.557	6.283
56	10.029	9.707	9.100	8.565	8.089	7.663	7.280	6.933	6.618	6.330	6.067
54	10.029	9.360	8.775	8.259	7.800	7.389	7.020	6.686	6.382	6.104	5.850
52	9.657	9.013	8.450	7.953	7.511	7.116	6.760	6.438	6.145	5.878	5.633
50	9.286	8.667	8.125	7.647	7.222	6.842	6.500	6.190	5.909	5.652	5.417
48	8.914	8.320	7.800	7.341	6.933	6.568	6.240	5.943	5.673	5.426	5.200
46	8.543	7.973	7.475	7.035	6.644	6.295	5.980	5.695	5.436	5.200	4.983
44	8.171	7.627	7.150	6.729	6.356	6.021	5.720	5.448	5.200	4.974	4.767